




PAN NETO
INTERNATIONAL
Edilizia italiana innovativa

Authentic - Diamonds - Originals				
	Measurement	EDGE	SURFACE	CLICK
 Plank	Different	MICRO BEVEL	EIR	 Warranty domestic use 20 Years
 Herringbone	Different	MICRO BEVEL	EIR	 Warranty domestic use 20 Years
Classification requirements EN 16511				
Performance classification - Classe di Utilizzo		EN ISO 10874	class 23-31-32-33-34	
 23	 31	 32	 33	 34
Wear resistance IP method A - Taber Test		ISO 24338 Procedure A	class 34	
Impact resistance		EN 13329:2006+A1:2008 Annex F	class 34	
Castor chair resistance		EN ISO 4918	class 34	
Effect of furniture leg		EN ISO 16581	Pass	
Residential indentation		EN ISO 24343-1	class 34	
Resistance to staining		EN 438-2 +A1	class 34	
Flexibility categories		EN ISO 178:2019,	Rigid	
General Requirements EN 16511				
Thickness in Total		EN 17539	4+1 and 5+1 and 5+1,5 mm	
Lenght		EN 17539	610 - 750 - 1220 - 1520 - 1820 mm	
Width		EN 17539	120 - 150 - 182 - 228 - 305 mm	
Lenght and width of squred elements		EN 17539	pass	
Squareness		EN 17539	pass	
Straightness		EN 17539	pass	
Flatness		EN 17539	pass	
General Characteristics EN 16511				
Openings		EN 17539	pass	
Height difference		EN 17539	pass	
Light fastness		EN ISO 105-B02:2014	> 6	
Dimensional stability under influence of temperature in x and y direction		TS EN ISO 23999	conformed	
Curling in z direction		TS EN ISO 23999	conformed	
CE certificate EN 14041				
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1	
	Emission of Formaldehyde	EN 717-1:2004	E1	
	Phatalate Analysis	Inhouse Method	Phatalate Free	
	Floor Heating System	Suitable	Max.27° C	
	Thermal Resistance	EN 12667	0.296 W/(m.K)	
	Slip Resistance	EN13893	DS	
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering	
More Technical Specification				
	Surface treatment	UV	YES	
	Thickness of wear layers	EN429	0.5mm	
	Underlay	IXPE	1,0 or 1,5 mm (kg/m³ 100)	
	Weight in total	EN ISO 23997	kgs/sqm - dipende dal modello	
More VOC test				
Antibacterial		ISO22196	Pass	
 FloorScore® standard Indoor Air quality Certified to SCS-EC10.3-2014 v4.1				
European Directive Limiting the VOC Content in Certain Products, 2004/42/EC			Pass	
Criteri Ambientali Minimi			Pass	



PAN NETO
INTERNATIONAL
Edilizia italiana innovativa

Wood Stone				
	Measurement	EDGE	SURFACE	CLICK
	Plank	Different	MICRO BEVEL	Wood
	Herringbone	Different	MICRO BEVEL	Wood
	Tile	Different	MICRO BEVEL	Stone
Classification requirements EN 16511				
Performance classification		EN ISO 10874	class 23-31-32	
				
Wear resistance IP method A - Taber Test		ISO 24338 Procedure A	class 32	
Impact resistance - Resistenza all'impatto		EN 13329-2006+A1:2008 Annex F	class 32	
Castor chair resistance		EN ISO 4918	class 32	
Effect of furniture leg		EN ISO 16581	Pass	
Residential indentation		EN ISO 24343-1	class 32	
Resistance to staining		EN 438-2 +A1	class 34	
Flexibility categories		EN ISO 178-2019,	Rigid	
General Requirements EN 16511				
Thickness in Total		EN 17539	4+1 and 5+1 and 5+1,5 mm	
Lenght		EN 17539	610 - 750 - 1220 - 1520 - 1820 mm	
Width		EN 17539	120 - 150 - 182 - 228 - 305 mm	
Lenght and width of squared elements		EN 17539	pass	
Squareness		EN 17539	pass	
Straightness		EN 17539	pass	
Flatness		EN 17539	pass	
General Characteristics EN 16511				
Openings		EN 17539	pass	
Height difference		EN 17539	pass	
Light fastness		EN ISO 105-B02:2014	> 6	
Dimensional stability under influence of temperature in x and y direction		TS EN ISO 23999	conformed	
Curling in z direction		TS EN ISO 23999	conformed	
CE certificate EN 14041				
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1	
	Emission of Formaldehyde	EN 717-1:2004	E1	
	Phatalate Analysis	Inhouse Method	Phatalate Free	
	Floor Heating System	Suitable	Max.27° C	
	Thermal Resistance	EN 12667	0.296 W/(m.K)	
	Slip Resistance	EN13893	DS	
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering	
More Technical Specification				
	Surface treatment	U/V	YES	
	Thickness of wear layers	EN429	0.3mm	
	Underlay	IXPE	1,0 or 1,5 mm (kg/m³ 100)	
	Weight in total	EN ISO 23997	kgs/sqm	
More VOC test				
Antibacterial		ISO22196	Pass	
		FloorScore® standard Indoor Air quality Certified to SCS-EC10.3-2014 v4.1		
European Directive Limiting the VOC Content in Certain Products, 2004/42/EC		Pass		
Criteri Ambientali Minimi		Pass		